
	<b>EAST COAST ORGANICS PRIVATE LIMITED</b> <b>237/2, Vellivoyal Chavadi, Chennai – 600 103</b> <b>Tamilnadu, India,</b>	DOC No : ECO/QC/TDS/001
		Issue Date : 01.10.2020
	<b>TECHNICAL DATA SHEET</b>  <b>MONOSULFIRAM - BP</b>	Rev No : 01
		Effective Date : 03.10.2020

Name of the Drug	:	Monosulfiram - BP 1993
Chemical Name	:	Tetra Ethyl Thiuram Monosulphide
CAS No	:	95-05-06
Molecular weight	:	264.5 g/mol
Molecular formula	:	C <sub>10</sub> H <sub>20</sub> N <sub>2</sub> S <sub>3</sub>

Product Specification		
S.No	Test	Specification
1	Description	Yellow or Yellowish Brown Liquid
2	Identification	a) Light Absorption in the Range 230 to 350 nm of 0.002 % w/v In Methanol exhibits a well defined Maximum only at 281nm. The absorption at 281nm is About 1.3
		b) Dissolve 0.1 gm in a mixture of 0.15 ml of a 1 % w/v Solution of copper II sulphate And 5 ml of ethanol (96 % ), Evaporate on a water bath and Dissolve the residue in Chloroform. A deep yellowish Brown colour is produce.
		c) Boil 0.1 g with 2M hydrochloric acid. Fumes are Evolved which turn lead Acetate paper black.
3	Related substances	Shall comply to the Requirements of BP 1993
4	Freezing point	28.5-32.0°C
5	Water	Not more than 1.0 % w/w
6	Sulphated ash	Not more than 0.1 % w/w
7	Assay By HPLC (on anhydrous basis)	98.00 - 101.00 %

	<b>EAST COAST ORGANICS PRIVATE LIMITED</b> <b>237/2, Vellivoyal Chavadi, Chennai – 600 103</b> <b>Tamilnadu, India,</b>	DOC No : ECO/QC/TDS/001
		Issue Date : 01.10.2020
	<b>TECHNICAL DATA SHEET</b>  <b>MONOSULFIRAM - BP</b>	Rev No : 01
		Effective Date : 03.10.2020

<b>Product Information</b>	
Solubility	Soluble in Acetone ,Toluene, Benzene, Carbon disulfide and Chloroform ; insoluble in water
Toxicity data	Dust may be irritating to the respiratory tract and cause symptoms of bronchitis. Harmful if swallowed. Repeat contact may cause skin sensitization. Toxic to aquatic organisms. Oral LD50/rat : 750 mg/kg
Handling and Personal Protection	Avoid breathing dust. Avoid contact with skin and eyes. Ensure good ventilation and local exhaustion of the working area. Wear suitable respiratory equipment, gloves with long cuffs, suitable protective clothing, Safety goggles recommended.
Storage	Should be a temperature of 8°C to 40°C and Protected from light

<b>Packaging</b>	
HDPE Barrel/Carbouy	Packed HDPE Carbouys , with shrink-wrapping.
Shelf Life	60 Months

Quality Assurance Manager

J.Kalimuthu - QA /QC